

- 5 4-INCH MINIMUM C.A.B. AT 95% COMPACTION OVER SUBGRADE AT 90% COMPACTION
- 6 SHALL BE A MINIMUM OF 4-FT AND SHALL NOT EXCEED 2% CROSS SLOPE FOR ADA COMPLIANCE
- T STRAIGHT GRADE FROM BACK OF CURB TO FRONT OF SIDEWALK. G2 MINUS G1 SHALL NOT EXCEED 12%. G1 MIN= -1%
- 8 EASEMENT BEYOND THE RIGHT-OF-WAY MAY BE REQUIRED TO ACCOMODATE THIS STANDARD'S REQUIREMENTS
- 9 RAMP ADJACENT SIDEWALK (8.33% MAX) TO ACCOMODATE NOTE #9. NO ADDITIONAL EASEMENT REQUIRED
- 9 ALT EASEMENT BEYOND THE RIGHT-OF-WAY MAY BE REQUIRED TO ACCOMODATE THIS STANDARD'S REQUIREMENTS

CITY OF CARSON

REVISIONS		COMMERCIAL	DRIVEWAY -	CASE 2	DRAWN BY:
INCLUDED 7-9ALT	12/21/16	RECOMMENDED:	APPROVED:		RAYMOND H. VELASCO, P.E.
DATE APPROVED: SHEET 1 OF 1		CITY ENGINEER	DIRECTOR OF P	UBLIC WORKS	NO. 112