



# City of Carson Report to Mayor and City Council

December 18, 2012  
New Business Consent

**SUBJECT: CONSIDER RESTRICTING THE USE OF CHAIN LINK FENCES IN THE FRONT OR SIDE YARDS FACING PUBLIC STREETS**

Submitted by Clifford W. Graves  
Director of Community Development

Approved by David C. Biggs  
City Manager

## **I. SUMMARY**

This item is on the agenda at the request of Mayor Dear.

The Carson Municipal Code (CMC) does not contain specific regulations related to the use of chain link fence material except in the CA (Commercial, Automotive) zone district. The Mayor has requested consideration of eliminating the use of chain link fence materials.

## **II. RECOMMENDATION**

TAKE the following actions:

1. REFER this item to the Planning Commission with direction to evaluate existing development standards related to fencing materials.
2. INITIATE an ordinance amendment, as deemed necessary, to provide appropriate regulations.

## **III. ALTERNATIVES**

TAKE another action the City Council deems appropriate.

## **IV. BACKGROUND**

Chain link fencing is an economical, permanent fencing that is often used in industrial areas. In some circumstances, chain link has also been used in residential and commercial areas. Some communities have specifically prohibited the use of chain link in areas that are visible from public streets.

The CMC provides various development standards for the location, height and design of fences, walls and hedges (Exhibit No. 1). The CA zone district expressly prohibits the use of chain link. Other zones do not generally specify the fence material unless the property is commercial or industrial and located adjacent to a residential zone. In such cases, a six-foot block wall is required. New development subject to CMC Section 9172.23 (Site Plan and Design Review) is often prohibited from using chain link fence material in the front or side yards facing public streets.

Establishing quality standards for all types of fences is important to maintain the architectural integrity of the community. The City Council should consider if existing standards provide an adequate level of review and regulation for current and future installation of fences. If there are perceived deficiencies, the City Council should provide direction to initiate additional study and the identification of potential regulations. Amending existing ordinances or establishing a fence permit requirement would require review and recommendation from the Planning Commission prior to consideration by the City Council.

**V. FISCAL IMPACT**

None.

**VI. EXHIBITS**

1. Excerpt from Carson Municipal Code Related to Fences, Wall and Hedges.  
(pgs. 3-6 )

Prepared by: Sheri Repp Loadsman, Planning Officer

TO: Rev09-04-2012

Reviewed by:

City Clerk	City Treasurer
Administrative Services	Public Works
Community Development	Community Services

**Action taken by City Council**

Date \_\_\_\_\_ Action \_\_\_\_\_

## **EXCERPT FROM CMC RELATED TO FENCE DEVELOPMENT STANDARDS**

### **Residential**

#### **9126.3 Fences, Walls and Hedges.**

A fence, wall or hedge shall not exceed a height of six (6) feet above the finished grade at each point along the fence, wall or hedge. Where there is a difference between the grades on the two (2) sides of the fence, wall or hedge, the higher grade shall be used.

The height limitation of this Section shall not apply in any case where it is in conflict with any other City ordinance or State law or regulation.

#### **9126.29 Encroachments Permitted in Required Yards and Open Spaces.**

Front Yard: Height above finished grade not more than 3-1/2', or as provided as condition of tract or parcel map approval, or as required by other laws.

Side or Rear Yard: Height above finished grade not more than 6', or as provided as condition of tract or parcel map approval, or as required by other laws.

Passageway: Any fence, wall or hedge across passageway to have at least 2-1/2' wide opening or gate.

### **Commercial**

#### **9136.3 Fences, Walls and Hedges.**

A solid masonry wall shall be placed along any lot line abutting or separated only by an alley from property in a residential zone. Except in a required front yard area and any abutting future right-of-way area, such wall shall be six (6) feet in height. In a required front yard area and any abutting future right-of-way area, such wall shall be three and one-half (3-1/2) feet in height, except fencing material of any type may extend above the three and one-half (3-1/2) foot solid masonry portion to a height not exceeding six (6) feet, provided such extended portion does not impair vision by obscuring more than ten (10) percent of the area in the vertical plane.

Except as required by other laws and regulations or as a condition of a tract or parcel map approval, no fence, wall or hedge in a commercial zone shall exceed a height of eight (8) feet.

The height of fences, walls and hedges shall be measured from the finished grade at each point along the fence, wall or hedge. Where there is a difference between the grade on the two (2) sides of the fence, wall or hedge, the higher grade shall be used.

The height and design of fences and walls within the CA Zone district shall be subject to CMC 9138.15(D). (Ord. 03-1279, § 13)

#### **9136.29(F) Encroachments.**

Every part of a required yard or open space shall be open and unobstructed from finished grade to the sky except for facilities and activities as follows:



F. Fences, walls and hedges are permitted as required by other laws or regulations or as a condition of a tract or parcel map approval, or shall not be higher than six (6) feet above finished grade in a future right-of-way area, front yard, side yard abutting a street, or yard abutting a residential zone. In a required front yard and any abutting future right-of-way area, any portion of a fence, wall or hedge above three and one-half (3-1/2) feet in height shall not impair vision by obscuring more than ten (10) percent of the area in the vertical plane.

**9138.15(D) Commercial, Automotive (CA) Development Standards.**

Walls/Fencing. Walls constructed on an interior lot line or at the rear of a required landscape setback of the CAD shall be in keeping with the regulations contained herein.

- a. Interior lot line walls shall not exceed eight (8) feet in height and rear walls shall not exceed twelve (12) feet in height. Use of barbed, razor or similar wire is prohibited.
- b. All service, storage and trash areas shall be screened from view from any public street by a wall. Trash enclosures shall be constructed to the City of Carson enclosure standards on file in the Planning Division.
- c. All walls shall be decorative, consisting of splitface masonry, slumpstone, stuccoed block, stone, wrought iron, or a combination thereof.
- d. Chainlink fencing is prohibited.

**9148.3(F) Retail Petroleum Outlets.**

F. Fencing.

- 1. A solid masonry wall, six (6) feet in height, shall be erected and maintained along any common boundary line with property in a residential zone, except that said wall shall not be less than two and one-half (2-1/2) feet or more than three and one-half (3-1/2) feet in height within the front yard required by CMC 9136.23.

**9138.10(C) Oil Wells.**

C. Fences, Walls and Hedges.

- 1. All oil well pumps and related facilities shall be enclosed with a fence not less than five (5) feet high mounted on steel posts with three (3) strands of barbed wire mounted at a forty-five (45) degree angle from the top of the fence. Such fence shall incorporate green vinyl coating of the fence mesh and wood or metal strips. The fence shall not be greater than two (2) inch mesh and not less than eleven (11) gauge wire. There shall be no aperture below the fence large enough to permit any child to crawl under.



2. The fence enclosure around the pump and related facilities shall include a twenty-five (25) foot buffer. The fence shall be locked at all times and constructed in a manner to prevent the public from coming closer than twenty-five (25) feet to the pumping facilities. Pursuant to the approval of the Conditional Use Permit, the location of the fence may be modified subject to compliance with applicable State and Fire Codes.

### **9146.3 Fences, Walls and Hedges.**

A. Except as provided in Division 8 of this Part\*:

1. A solid masonry wall shall be constructed along the inside of any lot line (or upon the lot line with the consent of the adjoining property owner) if the lot line abuts a residential zone or if the lot line abuts an alley that borders a residential zone. In areas other than the required front yard area and any abutting future right-of-way area, such wall shall be a minimum of six (6) feet and a maximum of eight (8) feet in height. In a required front yard area and any abutting future right-of-way area, such wall may not exceed three and one-half (3-1/2) feet in height, except fencing material of any type may extend above the three and one-half (3-1/2) foot solid masonry portion to a height not exceeding eight (8) feet, provided such extended portion does not impair vision by obscuring more than ten (10) percent of the area in the vertical plane.

2. No fence, wall or hedge in an industrial zone shall exceed a height of fifty (50) feet.

### **9148.1 Vehicle Dismantling Yards, Junk and Salvage Yards, Vehicle Impounding Yards.**

No vehicle dismantling yard, or junk and salvage yard, or vehicle impounding yard shall be established, maintained or extended in any zone unless it complies with the following requirements:

A. All operations and storage, including all equipment used in conducting such business, other than parking, shall be conducted within an enclosed building, or within an area enclosed by a solid fence. When two (2) or more vehicle dismantling yards, junk and salvage yards, and/or vehicle impounding yards have a common boundary line, a solid wall or solid fence shall not be required on such common boundary line; provided, however, that a solid wall or solid fence shall enclose the entire combined area devoted to such uses. (Ord. 80-532, § 6)

B. Where such fences or walls are provided, other than a decorative wall required pursuant to CMC 9162.52, they shall be developed as provided herein:

1. The fences and walls shall be of a uniform height in relation to the ground upon which they stand and shall be a minimum of eight (8) feet and shall not exceed fifteen (15) feet in height. Except in the yard areas where off-street parking is required or provided, said fences or walls shall be set back five (5) feet from the lot line along all frontages abutting a public street or walkway, or abutting a more restrictive zone. This five (5) foot setback area shall be landscaped in a neat, attractive manner and shall be equipped with an irrigation system, permanently and completely installed, which delivers water directly to all landscaped areas. Where off-street



parking is required or provided, said wall or fence shall be constructed at the rear of the parking area.

Tall-growing trees shall be planted and maintained alongside and rear fences or walls which abut an elevated freeway or residential area, in accordance with a planting plan approved by the Director.

2. All fences and walls open to view from any public street or walkway or any area in other than an industrial zone shall be constructed of solid masonry, except required fences may be constructed of other material comparable to the foregoing if approved by the Director and in accordance with standards established by resolution of the Council after recommendation by the Commission.

3. The fences and walls shall be constructed in workmanlike manner, shall be uniform in appearance and shall consist solely of new materials unless the Director approves the substitution of used materials, where, in his opinion, such used materials will provide the equivalent in service, appearance and useful life.

4. All gates in the fences or walls shall be of solid metal material and shall be no less than eight (8) feet in height and shall not exceed fifteen (15) feet in height. Such gates shall be kept closed when not in use and shall provide a pedestrian access opening unless other pedestrian access is provided.

3. The height of fences, walls and hedges shall be measured from the finished grade at each point along the fence, wall or hedge. Where there is a difference between the grade on the two (2) sides of the fence, wall or hedge, the higher grade shall be used. (Ord. 90-905, § 2)

\*Division 8 applies only to vehicle dismantling yards, junk and salvage yards, vehicle impounding yards, oil wells and retail petroleum outlets.

