



TYPICAL EXCAVATION SECTION

IF LESS THAN 3' REPLACE TO NEAREST JOINT
 IF LESS THAN 3' REPLACE TO CONSTRUCTION OR SAWED CONTRACTION JOINT

LEGEND

- EXCAVATION
- AREA OF CONCRETE PAVEMENT TO BE REPLACED
- SAW CUT 1-1/2" DEPTH

NOTES:

1. CONCRETE PAVEMENT SHALL NOT BE CUT WITHOUT PRIOR APPROVAL FROM PUBLIC WORKS DEPARTMENT EXCEPT FOR EMERGENCY REPAIRS.
2. CONCRETE PAVEMENT LESS THAN TWO YEARS OLD SHALL NOT BE CUT EXCEPT FOR EMERGENCY REPAIRS.
3. THE EXTENT OF REPAIR OF CONCRETE CUTS NOT SHOWN ON THIS STANDARD OR OF CUTS MADE WITHIN THREE FEET OF EXISTING PATCHES, CRACKS OR DETERIORATED SLABS SHALL BE DETERMINED BY PUBLIC WORKS DEPARTMENT.
4. ALL CONCRETE WORK SHALL CONFORM TO STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION. (LATEST EDITION).
5. ALL TRANSVERSE AND LONGITUDINAL JOINTS AND OUTER EDGES OF THE PAVEMENT WHICH ARE PART OF THE REPLACED CONCRETE SHALL BE EDGED WITH AN EDGING TOOL HAVING A RADIUS OF 1/4".
6. REPLACED CONCRETE THAT JOINS A SAWED EDGE OF THE EXISTING PAVEMENT SHALL NOT BE EDGED.
7. REPLACED CONCRETE SHALL BE FINISHED TO THE SAME SURFACE TEXTURE AS THAT OF ADJACENT EXISTING CONCRETE.
8. ALL CONCRETE CUTS, EXCEPT MIN. SIZED 3'X3' SERVICE CUTS, MADE UNDER ASPHALT SURFACING SHALL BE REPLACED IN KIND BEFORE REPLACING ASPHALT SURFACING. AT THE DISCRETION OF PUBLIC WORKS DEPARTMENT, THIS REQUIREMENT MAY BE WAIVED FOR TRANSVERSE CUTS 4' OR LESS IN WIDTH.

CITY OF CARSON

CONCRETE PAVEMENT REPLACEMENT

DRAWN BY *[Signature]*
 DATE APPROVED 2/2/87

RECOMMENDED: *[Signature]* APPROVED: *[Signature]*
 DIVISION ENGINEER DIRECTOR OF PUBLIC WORKS

NO. 127